

CIGWELD

AN ESAB BRAND

ARC WELDING INVERTERS

WeldSkill 140 | 180 | 200HF



CIGWELD.COM.AU

WeldSkill 200HF



Part No. W1008200

“ The ultimate portability in light TIG fabrication and stainless steel work! ”



The WeldSkill 200HF is a single phase welding inverter with a user-friendly control panel, practical push button operation for mode selection, clearly visible LED indicators and sturdy large control knob.

Affordable, compact and light-weight, this unit is a great addition to the workshop ensuring the ultimate portability in light TIG fabrication and stainless steel work for the Tradesman or Maintenance Worker.

The WeldSkill 200HF is supplied standard with features such as Arc Force, Down Slope Control (2T & 4T), Hot Start, Post Gas Flow and Anti-Stick. In addition to its appealing design and functional features, the WeldSkill 200HF provides the added reassurance of a high quality welding inverter that complies to Australian Standards. Simply plug it into any standard 15 Amp power point and get welding right away!

FEATURES



240 Volt, 15 Amp Supply Lead & Plug Fitted to Power Source.



Fully compliant to AS 60974.1-2006.



Max. Electrode Size 4.0mm. Suitable for All Electrode Types Except AWS E6010 Cellulose.



Over Temperature Cut Out Protection has been fitted to Power Source.



Anti Stick. Helps to prevent the stick electrode from sticking to the work piece.



Hot Start. Improves the arc start characteristics of stick electrodes.



Arc Force. Assists when stick welding in a tight corner or joint fit-up.



Current Range for this Power Source is 10A to 200A (TIG mode) of DC Welding Output.



3 Year Warranty* on Power Source
*Refer to Operation Manual for full details.



DC Lift TIG function. Provides smooth starting and running characteristics across a broad range of applications.



Power Source is fitted with HF Start Function in TIG mode for non contact TIG welding.



Rugged case with carry handle and carry strap.



4m Long Electrode Holder & Work Leads.



Twistlock Electrode Holder. Allows the electrode to be locked securely in place.

SPECIFICATIONS

DESCRIPTION	WELDSKILL 200HF
Part No	W1008200
Power Source Dimensions (excludes handle & gas inlet)	H245mm x W145mm x D420mm
Power Source Mass	8.2 KG
Cooling	Fan Cooled
Welder Type	HF TIG, Lift TIG and Stick Multi Process Inverter Power Source
Australian Standard	AS 60974.1-2006 / IEC 60974-1
Number of Phases	Single Phase
Nominal Supply Voltage	240 VAC \pm 10%
Nominal Supply Frequency	50/60 Hz
Welding Current Range - TIG	10 - 200 A
Welding Current Range - Stick	10 - 180 A
Nominal DC Open Circuit Voltage	75 V
Factory Fitted Supply Plug Rating	15 Amps
Effective Input Current (I _{1eff})	15 Amps
Maximum Input Current (I _{1max})	33.9 Amps
Minimum Single Phase Generator Recommendation	7.6 kW (9.5 kVA at 0.8 PF)
STICK (MMAW) Welding Output, 40°C, 10 min.	180 Amps @ 20% Duty Cycle
TIG (GTAW) Welding Output, 40°C, 10 min.	200 Amps @ 30% Duty Cycle
Protection Class	IP21S